

NAS1953T thru NAS1970T Series

Hex Head, Titanium Alloy, High Precision Aerospace Bolts

NAS1953T1	thru	NAS1953T100	(.1900-32 diameter)
NAS1954T1	thru	NAS1954T100	(.2500-28 diameter)
NAS1954T1	thru	NAS1955T100	(.3125-24 diameter)
NAS1956T1	thru	NAS1956T100	(.3750-24 diameter)
NAS1957T1	thru	NAS1957T100	(.4375-20 diameter)
NAS1958T1	thru	NAS1958T100	(.5000-20 diameter)
NAS1959T1	thru	NAS1959T100	(.5625-18 diameter)
NAS1960T1	thru	NAS1960T100	(.6250-18 diameter)
NAS1962T1	thru	NAS1962T100	(.7500-16 diameter)
NAS1964T1	thru	NAS1964T100	(.8750-14 diameter)
NAS1966T1	thru	NAS1966T100	(1.0000-12 diameter)
NAS1968T1	thru	NAS1968T100	(1.1250-12 diameter)
NAS1970T1	thru	NAS1970T100	(1.2500-12 diameter)

Material:

Titanium Alloy – 6Al-6V

Material Spec:

AMS4971

Tensile Strength:

180 KSI Min.

Hardness:

39-43 HRC

Finish:

No Finish (Clean and Degrease)

example: NAS1953T1

Aluminum Coated per NAS4006 and Halogen-free Cetyl Alcohol Lubricant

– add “P” suffix example: NAS1953T1P

Heat Treatment Spec:

AMS-H-81200 or AMS2801

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1953T1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS1953T1D

Drill 3 Corner Holes through Head for Safety Wire – add “H” suffix

example: NAS1953T1H

Drill 3 Holes through Head for Safety Wire and Drilled Shank for Cotter Pin

– add “DH” suffix example: NAS1953T1DH

Shank Diameter Options:

.0156 Oversize – add “X” suffix

example: NAS1953T1X

.0312 Oversize – add “Y” suffix

example: NAS1953T1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414