
NAS1953C thru NAS1970C Series

Hex Head, Alloy Steel, High Precision Aerospace Bolts

NAS1953C1	thru	NAS1953C100	(.1900-32 diameter)
NAS1954C1	thru	NAS1954C100	(.2500-28 diameter)
NAS1954C1	thru	NAS1955C100	(.3125-24 diameter)
NAS1956C1	thru	NAS1956C100	(.3750-24 diameter)
NAS1957C1	thru	NAS1957C100	(.4375-20 diameter)
NAS1958C1	thru	NAS1958C100	(.5000-20 diameter)
NAS1959C1	thru	NAS1959C100	(.5625-18 diameter)
NAS1960C1	thru	NAS1960C100	(.6250-18 diameter)
NAS1962C1	thru	NAS1962C100	(.7500-16 diameter)
NAS1964C1	thru	NAS1964C100	(.8750-14 diameter)
NAS1966C1	thru	NAS1966C100	(1.0000-12 diameter)
NAS1968C1	thru	NAS1968C100	(1.1250-12 diameter)
NAS1970C1	thru	NAS1970C100	(1.2500-12 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5732, AMS5737, AMS5853

Tensile Strength:

180 KSI Min.

Finish:

Clean and Passivate per AMS2700, METHOD 1, CLASS 4 – add “C” (remove hyphen)
example: NAS1953C1

Aluminum Coated per NAS4006 – add “P” suffix
example: NAS1953C1P

Heat Treatment Spec:

AS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1953C1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS1953C1D

Drill 3 Corner Holes through Head for Safety Wire – add “H” suffix

example: NAS1953C1H

Drill 3 Holes through Head for Safety Wire and Drilled Shank for Cotter Pin
– add “DH” suffix example: NAS1953C1DH

Shank Diameter Options:

.0156 Oversize – add “X” suffix

example: NAS1953C1X

.0312 Oversize – add “Y” suffix

example: NAS1953C1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414