

---

## NAS1972C thru NAS1980C Series

---

### 100 Degree Flush Head, Alloy Steel, High Precision Aerospace Bolts

NAS1972C1	thru	NAS1972C100	(.1640-32 diameter)
NAS1973C1	thru	NAS1973C100	(.1900-32 diameter)
NAS1974C1	thru	NAS1974C100	(.2500-28 diameter)
NAS1975C1	thru	NAS1975C100	(.3125-24 diameter)
NAS1976C1	thru	NAS1976C100	(.3750-24 diameter)
NAS1977C1	thru	NAS1977C100	(.4375-20 diameter)
NAS1978C1	thru	NAS1978C100	(.5000-20 diameter)
NAS1979C1	thru	NAS1979C100	(.5625-18 diameter)
NAS1980C1	thru	NAS1980C100	(.6250-18 diameter)

---

**Material:**

Alloy Steel – CRES A286

**Material Spec:**

AMS5731, AMS5732, AMS5737

**Tensile Strength:**

180 KSI Min.

**Hardness:**

36-40 HRC

**Finish Options:**

Clean and Passivated per AMS2700, METHOD 1, TYPE 2 or TYPE 8  
example: NAS1972C1

Aluminum Coated per NAS4006 – add “P” suffix  
example: NAS1972C1P

**Heat Treatment Spec:**

AMS-H-6875

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: NAS1972C1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS1972C1D

**Drive Option:**

Slotted Dovetail Recess – add “H” suffix  
example: NAS1972C1H

Offset Cruciform Recess – add “T” suffix  
example: NAS1972C1T

**Shank Option:**

.0156 Oversize – add “X” suffix  
example: NAS1972C1X

.0312 Oversize – add “Y” suffix  
example: NAS1972C1Y

*For inquiries or to place an order please call us at 718-847-6321.*