

---

## NAS1972T thru NAS1980T Series

---

### 100 Degree Flush Head, Titanium, High Precision Aerospace Bolts

NAS1972T1	thru	NAS1972T100	(.1640-32 diameter)
NAS1973T1	thru	NAS1973T100	(.1900-32 diameter)
NAS1974T1	thru	NAS1974T100	(.2500-28 diameter)
NAS1975T1	thru	NAS1975T100	(.3125-24 diameter)
NAS1976T1	thru	NAS1976T100	(.3750-24 diameter)
NAS1977T1	thru	NAS1977T100	(.4375-20 diameter)
NAS1978T1	thru	NAS1978T100	(.5000-20 diameter)
NAS1979T1	thru	NAS1979T100	(.5625-18 diameter)
NAS1980T1	thru	NAS1980T100	(.6250-18 diameter)

---

**Material:**

Titanium – 6Al-4V

**Material Spec:**

AMS4971

**Tensile Strength:**

180 KSI Min.

**Hardness:**

39-43 HRC

**Finish Options:**

Clean and Degrease with Halogen-free Cetyl Alcohol Lubricant

Aluminum Coated per NAS4006 and Halogen-free Cetyl Alcohol Lubricant

– add “P” suffix    example: NAS1972T1P

**Heat Treatment Spec:**

AMS-H-81200

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: NAS1972T1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS1972T1D

**Drive Option:**

Slotted Dovetail Recess – add “H” suffix

example: NAS1972T1H

Offset Cruciform Recess – add “T” suffix

example: NAS1972T1T

**Shank Option:**

.0156 Oversize – add “X” suffix

example: NAS1972T1X

.0312 Oversize – add “Y” suffix

example: NAS1972T1Y

*For inquiries or to place an order please call us at 718-847-6321.*

**FASTENER DIMENSIONS, INC.** ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414