
NAS1982C thru NAS1990C Series

Brazier Head, Alloy Steel, High Precision Aerospace Bolts

NAS1982C1	thru	NAS1982C100	(.1640-32 diameter)
NAS1983C1	thru	NAS1983C100	(.1900-32 diameter)
NAS1984C1	thru	NAS1984C100	(.2500-28 diameter)
NAS1985C1	thru	NAS1985C100	(.3125-24 diameter)
NAS1986C1	thru	NAS1986C100	(.3750-24 diameter)
NAS1987C1	thru	NAS1987C100	(.4375-20 diameter)
NAS1988C1	thru	NAS1988C100	(.5000-20 diameter)
NAS1989C1	thru	NAS1989C100	(.5625-18 diameter)
NAS1990C1	thru	NAS1990C100	(.6250-18 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5732, AMS5737, AMS5853

Tensile Strength:

180 KSI Min.

Hardness:

36-40 HRC

Finish Options:

Clean and Passivated per AMS2700

example: NAS1982C1D

Aluminum Coated per NAS4006 – add “P” suffix

example: NAS1982C1P

Heat Treatment Spec:

AMS-H-81200

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1982C1T

Drill Shank for Cotter Pin – add “D” suffix

example: NAS1982C1D

Drive Option:

None

example: NAS1982C1D

Slotted Dovetail Recess – add “H” suffix

example: NAS1982C1H

Offset Cruciform Recess – add “T” suffix

example: NAS1982C1T

Shank Option:

None

example: NAS1982C1D

.0156 Oversize – add “X” suffix

example: NAS1982C1TX

.0312 Oversize – add “Y” suffix

example: NAS1982C1TY

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414