

---

## NAS1982T thru NAS1990T Series

---

### Brazier Head, Titanium, High Precision Aerospace Bolts

NAS1982T1	thru	NAS1982T100	(.1640-32 diameter)
NAS1983T1	thru	NAS1983T100	(.1900-32 diameter)
NAS1984T1	thru	NAS1984T100	(.2500-28 diameter)
NAS1985T1	thru	NAS1985T100	(.3125-24 diameter)
NAS1986T1	thru	NAS1986T100	(.3750-24 diameter)
NAS1987T1	thru	NAS1987T100	(.4375-20 diameter)
NAS1988T1	thru	NAS1988T100	(.5000-20 diameter)
NAS1989T1	thru	NAS1989T100	(.5625-18 diameter)
NAS1990T1	thru	NAS1990T100	(.6250-18 diameter)

---

**Material:**

Titanium – 6Al-4V

**Material Spec:**

AMS4971

**Tensile Strength:**

180-200 KSI Min.

**Finish Options:**

No Finish (Clean and Degrease)

Aluminum Coated per NAS4006 – add “P” suffix

example: NAS1982T1P

**Heat Treatment Spec:**

AMS-H-81200

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: NAS1982T1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS1982T1D

**Drive Option:**

None

example: NAS1982T1

Slotted Dovetail Recess – add “H” suffix

example: NAS1982T1H

Offset Cruciform Recess – add “T” suffix

example: NAS1982T1T

**Shank Option:**

None

example: NAS1982T1

.0156 Oversize – add “X” suffix

example: NAS1982T1X

.0312 Oversize – add “Y” suffix

example: NAS1982T1Y

*For inquiries or to place an order please call us at 718-847-6321.*

**FASTENER DIMENSIONS, INC.** ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414