
NAS1992C thru NAS2000C Series

Flat 100 Degree Reduced Head, Alloy Steel, Precision Aerospace Bolts

NAS1992C1	thru	NAS1992C100	(.1640-32 diameter)
NAS1993C1	thru	NAS1993C100	(.1900-32 diameter)
NAS1994C1	thru	NAS1994C100	(.2500-28 diameter)
NAS1995C1	thru	NAS1995C100	(.3125-24 diameter)
NAS1996C1	thru	NAS1996C100	(.3750-24 diameter)
NAS1997C1	thru	NAS1997C100	(.4375-20 diameter)
NAS1998C1	thru	NAS1998C100	(.5000-20 diameter)
NAS1999C1	thru	NAS1999C100	(.5625-18 diameter)
NAS2000C1	thru	NAS2000C100	(.6250-18 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5737

Tensile Strength:

95 KSI Min.

Hardness:

36-40 HRC

Finish Options:

Clean and Passivated per AMS2700

example: NAS1992C1

Aluminum Coated per NAS4006 – add “P” suffix

example: NAS1992C1P

Heat Treatment Spec:

AMS-H-81200

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1992C1

Drill Threads for Cotter Pin – add “D” suffix

example: NAS1992C1D

Drive Option:

None

example: NAS1992C1

Hi-Torque Recess – add “H” suffix

example: NAS1992C1H

Torq-Set Recess – add “T” suffix

example: NAS1992C1T

Shank Option:

None

example: NAS1992C1

.0156 Oversize – add “X” suffix

example: NAS1992C1HX

.0312 Oversize – add “Y” suffix

example: NAS1992C1HY

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414