
NAS1992 thru NAS2000 Series

Flat 100 Degree Reduced Head, Alloy Steel, Precision Aerospace Bolts

NAS1992-1	thru	NAS1992-100	(.1640-32 diameter)
NAS1993-1	thru	NAS1993-100	(.1900-32 diameter)
NAS1994-1	thru	NAS1994-100	(.2500-28 diameter)
NAS1995-1	thru	NAS1995-100	(.3125-24 diameter)
NAS1996-1	thru	NAS1996-100	(.3750-24 diameter)
NAS1997-1	thru	NAS1997-100	(.4375-20 diameter)
NAS1998-1	thru	NAS1998-100	(.5000-20 diameter)
NAS1999-1	thru	NAS1999-100	(.5625-18 diameter)
NAS2000-1	thru	NAS2000-100	(.6250-18 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

MIL-S-5000, MIL-S-5626, MIL-S-6049

Tensile Strength:

95 KSI

Hardness:

36-40 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1992-1

Drill Threads for Cotter Pin – add “D” suffix

example: NAS1992-1D

Drive Option:

None

example: NAS1992-1

Hi-Torque Recess – add “H” suffix

example: NAS1992-1H

Torq-Set Recess – add “T” suffix

example: NAS1992-1T

Shank Option:

None

example: NAS1992-1

.0156 Oversize – add “X” suffix

example: NAS1992-1TX

.0312 Oversize – add “Y” suffix

example: NAS1992-1TY

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414