
NAS1992T thru NAS2000T Series

Flat 100 Degree Reduced Head, Titanium, Precision Aerospace Bolts

NAS1992T1	thru	NAS1992T100	(.1640-32 diameter)
NAS1993T1	thru	NAS1993T100	(.1900-32 diameter)
NAS1994T1	thru	NAS1994T100	(.2500-28 diameter)
NAS1995T1	thru	NAS1995T100	(.3125-24 diameter)
NAS1996T1	thru	NAS1996T100	(.3750-24 diameter)
NAS1997T1	thru	NAS1997T100	(.4375-20 diameter)
NAS1998T1	thru	NAS1998T100	(.5000-20 diameter)
NAS1999T1	thru	NAS1999T100	(.5625-18 diameter)
NAS2000T1	thru	NAS2000T100	(.6250-18 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4971

Tensile Strength:

95 KSI Min.

Hardness:

36-40 HRC

Finish Options:

(Clean and Degrease) with Halogen-free Cetyl Alcohol Lubricant

Aluminum Coated per NAS4006 with Halogen-free Cetyl Alcohol Lubricant
– add “P” suffix example: NAS1992T1P

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS1992T1

Drill Threads for Cotter Pin – add “D” suffix

example: NAS1992T1D

Drive Option:

None

example: NAS1992T1

Hi-Torque Recess – add “H” suffix

example: NAS1992T1H

Torq-Set Recess – add “T” suffix

example: NAS1992T1T

Shank Option:

None

example: NAS1992T1

.0156 Oversize – add “X” suffix

example: NAS1992T1HX

.0312 Oversize – add “Y” suffix

example: NAS1992T1HY

For inquiries or to place an order please call us at 718-847-6321.