
NAS28 Series

Tee Head, Alloy Steel, High Precision Aerospace Bolt

NAS28-3-1	thru	NAS28-3-100	(.1900-32 diameter)
NAS28-4-1	thru	NAS28-4-100	(.2500-28 diameter)
NAS28-5-1	thru	NAS28-5-100	(.3125-24 diameter)
NAS28-6-1	thru	NAS28-6-100	(.3750-24 diameter)
NAS28-7-1	thru	NAS28-7-100	(.4375-20 diameter)
NAS28-8-1	thru	NAS28-8-100	(.5000-20 diameter)
NAS28-10-1	thru	NAS28-10-100	(.6250-18 diameter)

Material:

Alloy Steel – 4130, 8630, 8735, 8740

Material Spec:

MIL-S-6049, MIL-S-6050, MIL-S-6098, MIL-S-6758

Tensile Strength:

125 KSI Min.

Hardness:

26.6 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 or Zinc Plate per QQ-Z-325, TYPE 1, CLASS 3

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

For inquiries or to place an order please call us at 718-847-6321.