
NAS2813 thru NAS2830 Series

Hex Head, Alloy Steel, High Precision Aerospace Bolts

NAS2813-1	thru	NAS2813-100	(.1900-32 diameter)
NAS2814-1	thru	NAS2814-100	(.2500-28 diameter)
NAS2815-1	thru	NAS2815-100	(.3125-24 diameter)
NAS2816-1	thru	NAS2816-100	(.3750-24 diameter)
NAS2817-1	thru	NAS2817-100	(.4375-20 diameter)
NAS2818-1	thru	NAS2818-100	(.5000-20 diameter)
NAS2819-1	thru	NAS2819-100	(.5625-18 diameter)
NAS2820-1	thru	NAS2820-100	(.6250-18 diameter)
NAS2822-1	thru	NAS2822-100	(.7500-16 diameter)
NAS2824-1	thru	NAS2824-100	(.8750-14 diameter)
NAS2826-1	thru	NAS2826-100	(1.0000-12 diameter)
NAS2828-1	thru	NAS2828-100	(1.1250-12 diameter)
NAS2830-1	thru	NAS2830-100	(1.1500-12 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

AMS6322, AMS6832, AMS6415, AMS6484

Tensile Strength:

180-200 KSI

Hardness:

39-43 HRC

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS2813-1

Drill Threads for Cotter Pin – add “D” suffix

example: NAS2813-1D

3 Corner Head Drill for Safety Wire – add “H” suffix

example: NAS2813-1H

Drill Threads for Cotter Pin and 3 Corner Head Drill for Safety Wire

– add “DH” suffix example: NAS2813-1DH

Shank Option:

None

example: NAS2813-1

.0156 Oversize – add “X” suffix

example: NAS2813-1X

.0312 Oversize – add “Y” suffix

example: NAS2813-1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414