

NAS2813T thru NAS2830T Series

Hex Head, Titanium, High Precision Aerospace Bolts

NAS2813T1	thru	NAS2813T100	(.1900-32 diameter)
NAS2814T1	thru	NAS2814T100	(.2500-28 diameter)
NAS2815T1	thru	NAS2815T100	(.3125-24 diameter)
NAS2816T1	thru	NAS2816T100	(.3750-24 diameter)
NAS2817T1	thru	NAS2817T100	(.4375-20 diameter)
NAS2818T1	thru	NAS2818T100	(.5000-20 diameter)
NAS2819T1	thru	NAS2819T100	(.5625-18 diameter)
NAS2820T1	thru	NAS2820T100	(.6250-18 diameter)
NAS2822T1	thru	NAS2822T100	(.7500-16 diameter)
NAS2824T1	thru	NAS2824T100	(.8750-14 diameter)
NAS2826T1	thru	NAS2826T100	(1.0000-12 diameter)
NAS2828T1	thru	NAS2828T100	(1.1250-12 diameter)
NAS2830T1	thru	NAS2830T100	(1.1500-12 diameter)

Material:

Titanium – 6Al-6V

Material Spec:

AMS4971

Tensile Strength:

180 KSI

Finish Options:

(Clean and Degrease) with Halogen-free Cetyl Alcohol Lubricant
example: NAS2813T1

without Halogen-free Cetyl Alcohol Lubricant – add “N” suffix
example: NAS2813T1N

Aluminum Coated per NAS4006 with Halogen-free Cetyl Alcohol Lubricant
– add “P” suffix example: NAS2813T1P

Aluminum Coated per NAS4006 **without** Halogen-free Cetyl Alcohol Lubricant
– add “NP” suffix example: NAS2813T1NP

Heat Treatment Spec:

AMS-H-81200, AMS2801

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole
example: NAS2813T1

Drill Threads for Cotter Pin – add “D” suffix
example: NAS2813T1D

3 Corner Head Drill for Safety Wire – add “H” suffix
example: NAS2813T1H

Drill Threads for Cotter Pin and 3 Corner Head Drill for Safety Wire
– add “DH” suffix example: NAS2813T1DH

Shank Option:

None
example: NAS2813T1

.0156 Oversize – add “X” suffix
example: NAS2813T1X

.0312 Oversize – add “Y” suffix
example: NAS2813T1Y

For inquiries or to place an order please call us at 718-847-6321.