
NAS2832C thru NAS2840C Series

100 Degree Flat Head, Alloy Steel, High Precision Aerospace Bolts

NAS2832C2	thru	NAS2832C96	(.1640-32 diameter)
NAS2833C2	thru	NAS2833C96	(.1900-32 diameter)
NAS2834C3	thru	NAS2834C96	(.2500-28 diameter)
NAS2835C3	thru	NAS2835C96	(.3125-24 diameter)
NAS2836C3	thru	NAS2836C96	(.3750-24 diameter)
NAS2837C4	thru	NAS2837C96	(.4375-20 diameter)
NAS2838C4	thru	NAS2838C96	(.5000-20 diameter)
NAS2839C5	thru	NAS2839C96	(.5625-18 diameter)
NAS2840C5	thru	NAS2840C96	(.6250-18 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5737

Tensile Strength:

180 KSI Min.

Hardness:

36-40 HRC

Finish Options:

Clean and Passivate per QQ-P-35 with Halogen-free Cetyl Alcohol Lubricant
example: NAS2832C1

Clean and Passivate per QQ-P-35 – add “N” suffix
example: NAS2832C1N

Aluminum Coated per NAS4006 with Halogen-free Cetyl Alcohol Lubricant
– add “P” suffix example: NAS2832C1P

Aluminum Coated per NAS4006 – add “NP” suffix
example: NAS2832C1NP

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole
example: NAS2832C1

Drill Shank for Cotter Pin – add “D” suffix
example: NAS2832C1D

Drive Option:

Slotted Dovetail Recess – add “H” suffix
example: NAS2832C1H

Offset Cruciform Recess – add “T” suffix
example: NAS2832C1T

Shank Option:

.0156 Oversize – add “X” suffix
example: NAS2832C1X

.0312 Oversize – add “Y” suffix
example: NAS2832C1Y

For inquiries or to place an order please call us at 718-847-6321.