
NAS2832T thru NAS2840T Series

100 Degree Flat Head, Titanium, High Precision Aerospace Bolts

NAS2832T2	thru	NAS2832T96	(.1640-32 diameter)
NAS2833T2	thru	NAS2833T96	(.1900-32 diameter)
NAS2834T3	thru	NAS2834T96	(.2500-28 diameter)
NAS2835T3	thru	NAS2835T96	(.3125-24 diameter)
NAS2836T3	thru	NAS2836T96	(.3750-24 diameter)
NAS2837T4	thru	NAS2837T96	(.4375-20 diameter)
NAS2838T4	thru	NAS2838T96	(.5000-20 diameter)
NAS2839T5	thru	NAS2839T96	(.5625-18 diameter)
NAS2840T5	thru	NAS2840T96	(.6250-18 diameter)

Material:

Titanium – 6Al-4V-2Sn

Material Spec:

AMS4971

Tensile Strength:

180 KSI Min.

Finish Options:

Clean and Degrease with Halogen-free Cetyl Alcohol Lubricant

Aluminum Coated per NAS4006 and Halogen-free Cetyl Alcohol Lubricant

– add “P” suffix example: NAS2832T1P

No Finish (Clean and Degrease) – add “N” suffix

example: NAS2832T1N

Aluminum Coated per NAS4006 – add “NP” suffix

example: NAS2832T1NP

Heat Treatment Spec:

AMS-H-81200

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS2832T1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS2832T1D

Drive Option:

Slotted Dovetail Recess – add “H” suffix

example: NAS2832T1H

Offset Cruciform Recess – add “T” suffix

example: NAS2832T1T

Shank Option:

.0156 Oversize – add “X” suffix

example: NAS2832T1X

.0312 Oversize – add “Y” suffix

example: NAS2832T1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414