
NAS2842 thru NAS2850 Series

100 Degree Crown Reduced Head, Alloy Steel, Precision Aerospace Bolts

NAS2842-1	thru	NAS2842-100	(.1640-32 diameter)
NAS2843-1	thru	NAS2843-100	(.1900-32 diameter)
NAS2844-1	thru	NAS2844-100	(.2500-28 diameter)
NAS2845-1	thru	NAS2845-100	(.3125-24 diameter)
NAS2846-1	thru	NAS2846-100	(.3750-24 diameter)
NAS2847-1	thru	NAS2847-100	(.4375-20 diameter)
NAS2848-1	thru	NAS2848-100	(.5000-20 diameter)
NAS2849-1	thru	NAS2849-100	(.5625-18 diameter)
NAS2850-1	thru	NAS2850-100	(.6250-18 diameter)

Material:

Alloy Steel – 4140, E4340, 8740

Material Spec:

AMS6415, MIL-S-5000, MIL-S-6049

Tensile Strength:

180-200 KSI Min.

Hardness:

39-43 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS2842-1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS2842-1D

Drive Option:

Slotted Dovetail Recess – add “H” suffix

example: NAS2842-1H

Offset Cruciform Recess – add “T” suffix

example: NAS2842-1T

Shank Option:

.0156 Oversize – add “X” suffix

example: NAS2842-1X

.0312 Oversize – add “Y” suffix

example: NAS2842-1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414