
NAS2842T thru NAS2850T Series

100 Degree Crown Reduced Head, Titanium, Precision Aerospace Bolts

NAS2842T1	thru	NAS2842T100	(.1640-32 diameter)
NAS2843T1	thru	NAS2843T100	(.1900-32 diameter)
NAS2844T1	thru	NAS2844T100	(.2500-28 diameter)
NAS2845T1	thru	NAS2845T100	(.3125-24 diameter)
NAS2846T1	thru	NAS2846T100	(.3750-24 diameter)
NAS2847T1	thru	NAS2847T100	(.4375-20 diameter)
NAS2848T1	thru	NAS2848T100	(.5000-20 diameter)
NAS2849T1	thru	NAS2849T100	(.5625-18 diameter)
NAS2850T1	thru	NAS2850T100	(.6250-18 diameter)

Material:

Titanium – 6Al-4V-2Sn

Material Spec:

AMS4971

Tensile Strength:

180 KSI Min.

Finish Options:

Clean and Degrease with Halogen-free Cetyl Alcohol Lubricant

Aluminum Coated per NAS4006 and Halogen-free Cetyl Alcohol Lubricant

– add “P” suffix example: NAS2842T1P

No Finish (Clean and Degrease) – add “N” suffix

example: NAS2842T1N

Aluminum Coated per NAS4006 – add “NP” suffix

example: NAS2842T1NP

Heat Treatment Spec:

AMS-H-81200

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS2842T1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS2842T1D

Drive Option:

Slotted Dovetail Recess – add “H” suffix

example: NAS2842T1H

Offset Cruciform Recess – add “T” suffix

example: NAS2842T1T

Shank Option:

.0156 Oversize – add “X” suffix

example: NAS2842T1X

.0312 Oversize – add “Y” suffix

example: NAS2842T1Y

For inquiries or to place an order please call us at 718-847-6321.