
NAS2852C thru NAS2860C Series

100 Degree Crown Reduced Head, Alloy Steel, Precision Aerospace Bolts

NAS2852C1	thru	NAS2852C100	(.1640-32 diameter)
NAS2853C1	thru	NAS2853C100	(.1900-32 diameter)
NAS2854C1	thru	NAS2854C100	(.2500-28 diameter)
NAS2855C1	thru	NAS2855C100	(.3125-24 diameter)
NAS2856C1	thru	NAS2856C100	(.3750-24 diameter)
NAS2857C1	thru	NAS2857C100	(.4375-20 diameter)
NAS2858C1	thru	NAS2858C100	(.5000-20 diameter)
NAS2859C1	thru	NAS2859C100	(.5625-18 diameter)
NAS2860C1	thru	NAS2860C100	(.6250-18 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5737

Tensile Strength:

180 KSI Min.

Hardness:

36-40 HRC

Finish Options:

Clean and Passivate per QQ-P-35 with Halogen-free Cetyl Alcohol Lubricant
example: NAS2852C1

Clean and Passivate per QQ-P-35 – add “N” to suffix
example: NAS2852C1NX

Aluminum Coated per NAS4006 with Halogen-free Cetyl Alcohol Lubricant
– add “P” to suffix example: NAS2852C1PX

Aluminum Coated per NAS4006 – add “NP” to suffix
example: NAS2852C1NPX

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole
example: NAS2852C1

Drill Shank for Cotter Pin – add “D” suffix
example: NAS2852C1D

Drive Option:

Slotted Dovetail Recess – add “H” suffix
example: NAS2852C1H

Offset Cruciform Recess – add “T” suffix
example: NAS2852C1T

Shank Option:

.0156 Oversize – add “X” suffix
example: NAS2852C1HX

.0312 Oversize – add “Y” suffix
example: NAS2852C1HY

For inquiries or to place an order please call us at 718-847-6321.