
NAS2852 thru NAS2860 Series

100 Degree Crown Reduced Head, Alloy Steel, Precision Aerospace Bolts

NAS2852-1	thru	NAS2852-100	(.1640-32 diameter)
NAS2853-1	thru	NAS2853-100	(.1900-32 diameter)
NAS2854-1	thru	NAS2854-100	(.2500-28 diameter)
NAS2855-1	thru	NAS2855-100	(.3125-24 diameter)
NAS2856-1	thru	NAS2856-100	(.3750-24 diameter)
NAS2857-1	thru	NAS2857-100	(.4375-20 diameter)
NAS2858-1	thru	NAS2858-100	(.5000-20 diameter)
NAS2859-1	thru	NAS2859-100	(.5625-18 diameter)
NAS2860-1	thru	NAS2860-100	(.6250-18 diameter)

Material:

Alloy Steel – 4340, 8740

Material Spec:

AMS6322, MIL-S-6049, MIL-S-6322

Tensile Strength:

180 KSI Min.

Hardness:

39-43 HRC

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS2852-1

Drill Shank for Cotter Pin – add “D” to suffix

example: NAS2852-1DX

Drive Option:

Slotted Dovetail Recess – add “H” suffix

example: NAS2852-1DHX

Offset Cruciform Recess – add “T” suffix

example: NAS2852-1DTX

Shank Option:

.0156 Oversize – add “X” suffix

example: NAS2852-1X

.0312 Oversize – add “Y” suffix

example: NAS2852-1Y

For inquiries or to place an order please call us at 718-847-6321.