
NAS2852T thru NAS2860T Series

100 Degree Crown Reduced Head, Titanium, Precision Aerospace Bolts

NAS2852T1	thru	NAS2852T100	(.1640-32 diameter)
NAS2853T1	thru	NAS2853T100	(.1900-32 diameter)
NAS2854T1	thru	NAS2854T100	(.2500-28 diameter)
NAS2855T1	thru	NAS2855T100	(.3125-24 diameter)
NAS2856T1	thru	NAS2856T100	(.3750-24 diameter)
NAS2857T1	thru	NAS2857T100	(.4375-20 diameter)
NAS2858T1	thru	NAS2858T100	(.5000-20 diameter)
NAS2859T1	thru	NAS2859T100	(.5625-18 diameter)
NAS2860T1	thru	NAS2860T100	(.6250-18 diameter)

Material:

Titanium – 6Al-4V-2Sn

Material Spec:

AMS4971

Tensile Strength:

180 KSI Min.

Finish Options:

Clean and Degrease with Halogen-free Cetyl Alcohol Lubricant

Aluminum Coated per NAS4006 and Halogen-free Cetyl Alcohol Lubricant

– add “P” suffix example: NAS2852T1P

No Finish (Clean and Degrease) – add “N” suffix

example: NAS2852T1N

Aluminum Coated per NAS4006 – add “NP” to suffix

example: NAS2852T1DHNPX

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS2852T1

Drill Shank for Cotter Pin – add “D” to suffix

example: NAS2852T1DN

Drive Option:

Slotted Dovetail Recess – add “H” suffix

example: NAS2852T1H

Offset Cruciform Recess – add “T” suffix

example: NAS2852T1NT

Shank Option:

.0156 Oversize – add “X” suffix

example: NAS2852T1DX

.0312 Oversize – add “Y” suffix

example: NAS2852T1DY

For inquiries or to place an order please call us at 718-847-6321.