
NAS2903 thru NAS2920 Series

Hex Head, Alloy Steel, High Precision Aerospace Bolts

NAS2903-1	thru	NAS2903-100	(.1900-32 diameter)
NAS2904-1	thru	NAS2904-100	(.2500-28 diameter)
NAS2905-1	thru	NAS2905-100	(.3125-24 diameter)
NAS2906-1	thru	NAS2906-100	(.3750-24 diameter)
NAS2907-1	thru	NAS2907-100	(.4375-20 diameter)
NAS2908-1	thru	NAS2908-100	(.5000-20 diameter)
NAS2909-1	thru	NAS2909-100	(.5625-18 diameter)
NAS2910-1	thru	NAS2910-100	(.6250-18 diameter)
NAS2912-1	thru	NAS2912-100	(.7500-16 diameter)
NAS2914-1	thru	NAS2914-100	(.8750-14 diameter)
NAS2916-1	thru	NAS2916-100	(1.0000-12 diameter)
NAS2918-1	thru	NAS2918-100	(1.1250-12 diameter)
NAS2920-1	thru	NAS2920-100	(1.2500-12 diameter)

Material:

Alloy Steel – 4340, 8740

Material Spec:

AMS6322, AMS6415, AMS6484, MIL-S-6049

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

AMS2759

Thread Options:

Long Thread

example: NAS2903-1

Short Thread – add “E” (replace hyphen)

example: NAS2903E1

Drilling Options:

No Hole

example: NAS2903-1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS2903-1D

Drill 3 Corner Holes through Head for Safety Wire – add “H” suffix

example: NAS2903-1H

Drill 3 Holes through Head for Safety Wire and Drilled Shank for Cotter Pin

– add “DH” suffix example: NAS2903-1DH

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414