
NAS3003 thru NAS3020 Series

Hex Head, Alloy Steel, High Precision Aerospace Bolts

NAS3003-1	thru	NAS3003-100	(.1900-32 diameter)
NAS3004-1	thru	NAS3004-100	(.2500-28 diameter)
NAS3005-1	thru	NAS3005-100	(.3125-24 diameter)
NAS3006-1	thru	NAS3006-100	(.3750-24 diameter)
NAS3007-1	thru	NAS3007-100	(.4375-20 diameter)
NAS3008-1	thru	NAS3008-100	(.5000-20 diameter)
NAS3009-1	thru	NAS3009-100	(.5625-18 diameter)
NAS3010-1	thru	NAS3010-100	(.6250-18 diameter)
NAS3012-1	thru	NAS3012-100	(.7500-16 diameter)
NAS3014-1	thru	NAS3014-100	(.8750-14 diameter)
NAS3016-1	thru	NAS3016-100	(1.0000-12 diameter)
NAS3018-1	thru	NAS3018-100	(1.1250-12 diameter)
NAS3020-1	thru	NAS3020-100	(1.2500-12 diameter)

Material:

Alloy Steel – 4340, 8740

Material Spec:

AMS6322, AMS6415, AMS6484, MIL-S-6049

Tensile Strength:

160-180 KSI Min.

Hardness:

36-40 HRC

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

AMS2759

Thread Options:

Standard Thread

example: NAS3003-1

Short Thread – add “E” (replace hyphen)

example: NAS3003E1

Drilling Options:

No Hole

example: NAS3003-1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS3003-1D

Drill 3 Corner Holes through Head for Safety Wire – add “H” suffix

example: NAS3003-1H

Drill 3 Holes through Head for Safety Wire and Drilled Shank for Cotter Pin

– add “DH” suffix example: NAS3003-1DH

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414