

---

## NAS333 thru NAS340 Series

---

### Shear 100 Degree Flush Head, Alloy Steel, Machine Screws

NAS333-10	thru	NAS333-100	(.1900-32 diameter)
NAS334-10	thru	NAS334-100	(.2500-28 diameter)
NAS335-10	thru	NAS335-100	(.3125-24 diameter)
NAS336-10	thru	NAS336-100	(.3750-24 diameter)
NAS337-10	thru	NAS337-100	(.4375-20 diameter)
NAS338-10	thru	NAS338-100	(.5000-20 diameter)
NAS339-10	thru	NAS339-100	(.5625-18 diameter)
NAS340-10	thru	NAS340-100	(.6250-18 diameter)

---

#### Material:

Alloy Steel – 4140, 4340, 8740

#### Material Spec:

AMS6322, AMS6327, AMS6349, AMS6414, AMS6415, AMS6832, AMS6484

#### Tensile Strength:

160-180 KSI Min.

#### Finish Options:

None

example: NAS333-10

Cadmium Plated Shank – add “C” (replace hyphen)

example: NAS333C10

#### Heat Treatment Spec:

AMS2759

#### Drilling Options:

No Hole

example: NAS333-10

Drill Shank for Cotter Pin – add “A” suffix

example: NAS333CPA10

#### Thread:

Full Thread

#### Grip Length Option:

Standard Length

example: NAS333C10

.062 Oversize– add “-5” dash plus number suffix

example: NAS333C10-5

#### Drive Option:

Hexagon Socket

example: NAS333C10

Cruciform Recess – add “P” to basic part number

example: NAS333CPA10

*For inquiries or to place an order please call us at 718-847-6321.*

**FASTENER DIMENSIONS, INC.** ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414