
NAS4450S Series

Protruding Shear Head, Alloy Steel, Crimp Pin

NAS4450S05-01	thru	NAS4450S05-20	(.1640-32 diameter)
NAS4450S06-01	thru	NAS4450S06-24	(.1900-32 diameter)
NAS4450S08-01	thru	NAS4450S08-28	(.2500-28 diameter)
NAS4450S10-02	thru	NAS4450S10-30	(.3125-24 diameter)
NAS4450S12-02	thru	NAS4450S12-32	(.3750-24 diameter)

Material:

Alloy Steel – 4340, 8740

Material Spec:

AMS-QQ-P-416, TYPE 2, CLASS 2

Tensile Strength:

108 KSI Min.

Finish Options:

Cadmium Plated per AMS-QQ-P-416, TYPE 2, CLASS 2

example: NAS4450S05-10

Diffused Nickel-Cadmium Plate (for high strength and/or temps. over 450 degrees F)

– add “**N**” (replace hyphen) example: NAS4450S05N10

Lubrication Options:

None

example: NAS4450S05-10

Dry Film Lubricant per AS5272, TYPE 1 or Molybdenum Disulfide per AMS-M-7866

– add “**E**” suffix example: NAS4450S05-10E

Chlorine-free Cetyl Alcohol per AS18732, TYPE 1, GRADE B

– add “**P**” suffix example: NAS4450S05-10P

Oversize Option:

Optional Oversize Shank Diameter – add “**R**” suffix

example: 4450S05-10R

For inquiries or to place an order please call us at 718-847-6321.