
NAS4450V Series

Protruding Shear Head, Titanium, Crimp Pin

NAS4450V05-01	thru	NAS4450V05-20	(.1640-32 diameter)
NAS4450V06-01	thru	NAS4450V06-24	(.1900-32 diameter)
NAS4450V08-01	thru	NAS4450V08-28	(.2500-28 diameter)
NAS4450V10-02	thru	NAS4450V10-30	(.3125-24 diameter)
NAS4450V12-02	thru	NAS4450V12-32	(.3750-24 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

UNS R6400

Tensile Strength:

95 KSI Min.

Finish Options:

None

example: NAS4450V05-10

Diffused Nickel-Cadmium Plate (for high strength and/or temps. over 450 degrees F)

– add “N” (replace hyphen) example: NAS4450V05N10

Lubrication Options:

None

example: NAS4450V05-10

Dry Film Lubricant per AS5272, TYPE 1 or Molybdenum Disulfide per AMS-M-7866

– add “E” suffix example: NAS4450V05-10E

Chlorine-free Cetyl Alcohol per AS18732, TYPE 1, GRADE B

– add “P” suffix example: NAS4450V05-10P

Oversize Option:

Optional Oversize Shank Diameter – add “R” suffix

example: 4450V05-10R

For inquiries or to place an order please call us at 718-847-6321.