
NAS4703 thru NAS4716 Series

100 Degree Reduced Head, Alloy Steel, Short Thread Aerospace Bolts

NAS4703-1	thru	NAS4703-100	(.1900-32 diameter)
NAS4704-2	thru	NAS4704-100	(.2500-28 diameter)
NAS4705-2	thru	NAS4705-100	(.3125-24 diameter)
NAS4706-2	thru	NAS4706-100	(.3750-24 diameter)
NAS4707-2	thru	NAS4707-100	(.4375-20 diameter)
NAS4708-3	thru	NAS4708-100	(.5000-20 diameter)
NAS4709-3	thru	NAS4709-100	(.5625-18 diameter)
NAS4710-3	thru	NAS4710-100	(.6250-18 diameter)
NAS4712-4	thru	NAS4712-100	(.7500-14 diameter)
NAS4714-5	thru	NAS4714-100	(.8750-14 diameter)
NAS4716-6	thru	NAS4716-100	(1.0000-12 diameter)

Material:

Alloy Steel – 4340

Material Spec:

MIL-S-6758

Tensile Strength:

160-180 KSI Min.

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2
Embrittlement requirements per NAS4002

Heat Treatment Spec:

MIL-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

Drill Shank for Cotter Pin – add “**D**” replace hyphen
example: NAS4703D1

Undrilled Head and Shank –

example: NAS4703-1

Drive Recess:

Tri-Slot Recess per NAS4000

Deep Number Four Recess – add “**J**” as fifth digit to basic part number

example: NAS4703JD1

For inquiries or to place an order please call us at 718-847-6321.