

---

## NAS495 Series

---

### Hex Head, Internal Wrenching, Alloy Steel, Aerospace Bolts

NAS495-4-10	thru	NAS495-4-130	(.2500-28 diameter)
NAS495-5-10	thru	NAS495-5-130	(.3125-24 diameter)
NAS495-6-10	thru	NAS495-6-130	(.3750-24 diameter)
NAS495-7-10	thru	NAS495-7-130	(.4375-20 diameter)
NAS495-8-10	thru	NAS495-8-130	(.5000-20 diameter)
NAS495-9-10	thru	NAS495-9-130	(.5625-18 diameter)
NAS495-10-10	thru	NAS495-10-130	(.6250-18 diameter)
NAS495-12-10	thru	NAS495-12-130	(.7500-16 diameter)
NAS495-14-10	thru	NAS495-14-130	(.8750-14 diameter)
NAS495-16-10	thru	NAS495-16-130	(1.0000-14 diameter)
NAS495-18-10	thru	NAS495-18-130	(1.1250-12 diameter)
NAS495-20-10	thru	NAS495-20-130	(1.2500-12 diameter)
NAS495-22-10	thru	NAS495-22-130	(1.3750-12 diameter)
NAS495-24-10	thru	NAS495-24-130	(1.5000-12 diameter)

---

#### Material:

Alloy Steel – 4140, 4340, 8740

#### Material Spec:

MIL-S-5626, MIL-S-5000, MIL-S-8503, MIL-S-6098, MIL-S-6049

#### Tensile Strength:

160 KSI Min.

#### Hardness:

34-40 HRC

#### Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

#### Thread Length:

Available in the entire range of standard lengths

#### Drilling Options:

None

example: NAS495-4-10

Drilled Head for Safety Wire – add “H” (replace hyphen)

example: NAS495H4-10

*For inquiries or to place an order please call us at 718-847-6321.*