
NAS501 Series

Hex Head, Stainless Steel, High Precision Aerospace Bolts

NAS501-3-1	thru	NAS501-3-100	(.1900-32 diameter)
NAS501-4-1	thru	NAS501-4-100	(.2500-28 diameter)
NAS501-5-1	thru	NAS501-5-100	(.3125-24 diameter)
NAS501-6-1	thru	NAS501-6-100	(.3750-24 diameter)
NAS501-7-1	thru	NAS501-7-100	(.4375-20 diameter)
NAS501-8-1	thru	NAS501-8-100	(.5000-20 diameter)
NAS501-9-1	thru	NAS501-9-100	(.5625-18 diameter)
NAS501-10-1	thru	NAS501-10-100	(.6250-18 diameter)
NAS501-12-1	thru	NAS501-12-100	(.7500-16 diameter)
NAS501-14-1	thru	NAS501-14-100	(.8750-14 diameter)
NAS501-16-1	thru	NAS501-16-100	(1.0000-14 diameter)
NAS501-18-1	thru	NAS501-18-100	(1.1250-12 diameter)
NAS501-20-1	thru	NAS501-20-100	(1.2500-12 diameter)

Material:

Stainless Steel – CRES 321 or 347

Material Spec:

AMS5645, AMS5646

Tensile Strength:

85 KSI Min.

Finish:

Passivated per QQ-P-35 or AMS2700

Heat Treatment Spec:

AS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

Drill Shank for Cotter Pin

example: NAS501-3-1

No Hole – add “**A**” suffix

example: NAS501-3-1A

Drill 1 Hole through Head for Safety Wire – add “**H**” (replace hyphen) and “**A**” suffix

example: NAS501-3H1A

Drill Head for Safety Wire and Drilled Shank for Cotter Pin – add “**H**” (replace hyphen)

example: NAS501-3H1

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414