

---

## NAS5300 thru NAS5306 Series

---

### Flat Fillister Head, Full Thread, Alloy Steel, Machine Screw

|           |      |             |                     |
|-----------|------|-------------|---------------------|
| NAS5300-1 | thru | NAS5300-100 | (.1120-40 diameter) |
| NAS5301-1 | thru | NAS5301-100 | (.1380-32 diameter) |
| NAS5302-1 | thru | NAS5302-100 | (.1640-32 diameter) |
| NAS5303-1 | thru | NAS5303-100 | (.1900-32 diameter) |
| NAS5304-1 | thru | NAS5304-100 | (.2500-28 diameter) |
| NAS5305-1 | thru | NAS5305-100 | (.3125-24 diameter) |
| NAS5306-1 | thru | NAS5306-100 | (.3750-24 diameter) |

---

**Material:**

Alloy Steel

**Material Spec:**

MIL-F-18240, QPL-18240

**Tensile Strength:**

160-180 KSI Min.

**Finish Options:**

Cadmium Plated per AMS-QQ-P-416, TYPE 2, CLASS 2

example: NAS5303-10

Cadmium Plated with Black color per Unichrome® Dip Bulletin P-65-B-Cd

– add “B” (replace hyphen) example: NAS5303B10

**Heat Treatment Spec:**

AMS2759

**Thread:**

Full Thread

**Drilling Options:**

No Hole

example: NAS5303-10

Drilled Head for Safety Wire – add “H” (replace hyphen)

example: NAS5303H10

**Self-Locking Element:**

Non-Locking

example: NAS5303-10

Optional Locking Element – add “L” (replace hyphen)

example: NAS5303L10

Patch Type Locking Element – add “P” (replace hyphen)

example: NAS5303P10

**Drive Recess Options:**

Tri-Wing® Recess

example: NAS5303-10

Deep Number 4 Recess – add “J” (replace hyphen)

example: NAS5303JB10

*For inquiries or to place an order please call us at 718-847-6321.*

**FASTENER DIMENSIONS, INC.** ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414