
NAS5311V Series

Flat Fillister Head, Titanium, High Precision Aerospace Screws

| | | | |
|--------------|------|----------------|---------------------|
| NAS1219V04-1 | thru | NAS1219V04-100 | (.1120-40 diameter) |
| NAS1219V06-1 | thru | NAS1219V06-100 | (.1380-32 diameter) |
| NAS1219V08-1 | thru | NAS1219V08-100 | (.1640-32 diameter) |
| NAS1219V3-1 | thru | NAS1219V3-100 | (.1900-32 diameter) |
| NAS1219V4-1 | thru | NAS1219V4-100 | (.2500-28 diameter) |
| NAS1219V5-1 | thru | NAS1219V5-100 | (.3125-24 diameter) |
| NAS1219V6-1 | thru | NAS1219V6-100 | (.3750-24 diameter) |

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AM4967

Tensile Strength:

160 KSI Min.

Finish:

No Finish (Clean and Degrease)

example: NAS5311V3-15

Aluminum Coated per NAS4006 and Halogen-free Cetyl Alcohol Lubricant per AS87132, TYPE 3, GRADE B – add “A” (replace hyphen)

example: NAS5311V3A15

Heat Treatment Spec:

AMS-H-81200, AMS2801

Thread Length:

Full Thread

Drilling Options:

No Hole

example: NAS5311V3-15

Drill Head for Safety Wire – add “H” suffix

example: NAS5311V3-15H

Self-Locking Options:

None

example: NAS5311V04-1

Patch Type Locking Element – add “J” add suffix

example: NAS5311V04-1J

Recess:

Six Lobe Recess

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414