
NAS5314E Series

Shear Pan Head, Alloy Steel, Close Tolerance Aerospace Screws

NAS5314E06-1	thru	NAS5314E06-100	(.1380-32 diameter)
NAS5314E08-1	thru	NAS5314E08-100	(.1640-32 diameter)
NAS5314E3-1	thru	NAS5314E3-100	(.1900-32 diameter)
NAS5314E4-1	thru	NAS5314E4-100	(.2500-28 diameter)
NAS5314E5-1	thru	NAS5314E5-100	(.3125-24 diameter)
NAS5314E6-1	thru	NAS5314E6-100	(.3750-24 diameter)
NAS5314E8-1	thru	NAS5314E8-100	(.5000-20 diameter)

Material:

CRES – A286

Material Spec:

AMS5731, AMS5732, AMS5737, AMS5853

Tensile Strength:

160-190 KSI Min.

Finish Options:

Passivated per AMS2700, METHOD 1, TYPE 1 or TYPE 8, CLASS 1
example: NAS5314E3-10

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” suffix
example: NAS5314E3P10

Heat Treatment Spec:

AMS-H-6875, AMS2759

Thread Length:

Short Thread

Recess:

Six Lobe Recess

For inquiries or to place an order please call us at 718-847-6321.