
NAS5317V Series

Pan Head, Titanium, Full Thread, Aerospace Screw

NAS5317V02-1	thru	NAS5317V02-100	(.0860-56 diameter)
NAS5317V04-1	thru	NAS5317V04-100	(.1120-40 diameter)
NAS5317V06-1	thru	NAS5317V06-100	(.1380-32 diameter)
NAS5317V08-1	thru	NAS5317V08-100	(.1640-32 diameter)
NAS5317V3-1	thru	NAS5317V3-100	(.1900-32 diameter)
NAS5317V4-1	thru	NAS5317V4-100	(.2500-28 diameter)
NAS5317V5-1	thru	NAS5317V5-100	(.3125-24 diameter)
NAS5317V6-1	thru	NAS5317V6-100	(.3750-24 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

None

example: NAS5317V3-1

Aluminum Coated per NAS4006 and Halogen-free Cetyl Alcohol Lubricant per AS87132, TYPE 3, GRADE B – add “A” after second dash

example: NAS5317V3A10

Heat Treatment Spec:

AMS-H-81200, AMS2801

Thread Length:

Full Thread

Self-Locking Options:

None

example: NAS5317V3-1

Patch Type Locking Element – add “J” add suffix

example: NAS5317V5A15J

Drive Resess:

Six Lobe Recess

For inquiries or to place an order please call us at 718-847-6321.