

---

## NAS5318V Series

---

### Flat Pan Head, Titanium, Close Tolerance, Long Thread, Shear Bolts

|             |      |              |                     |
|-------------|------|--------------|---------------------|
| NAS5318V3-1 | thru | NAS5318V3-96 | (.1900-32 diameter) |
| NAS5318V4-1 | thru | NAS5318V4-96 | (.2500-28 diameter) |
| NAS5318V5-1 | thru | NAS5318V5-96 | (.3125-24 diameter) |
| NAS5318V6-4 | thru | NAS5318V6-96 | (.3750-24 diameter) |
| NAS5318V7-4 | thru | NAS5318V7-96 | (.4375-20 diameter) |
| NAS5318V8-4 | thru | NAS5318V8-96 | (.5000-20 diameter) |

---

**Material:**

Titanium – 6Al-4V

**Material Spec:**

AMS4928, AMS4967

**Tensile Strength:**

160 KSI Min.

**Hardness:**

36-40 HRC

**Finish:**

No Finish (Clean and Degrease)

example: NAS5318V3-1

Aluminum Coated per NAS4006 and Halogen-free Cetyl Alcohol Lubricant

– add “A” suffix example: NAS5318V3-1A

**Heat Treatment Spec:**

AMS-H-81200, AMS2801

**Thread Length:**

Available in the entire range of standard lengths

**Drive Resess:**

Six Lobe Recess

**Self-Locking Options:**

None

example: NAS5318V3-1

Self-Locking Element – add “J” add suffix

example: NAS5318V3-1J

*For inquiries or to place an order please call us at 718-847-6321.*