
NAS5319V Series

100 Degree Flush Head, Titanium, Close Tolerance, Shear Screw

NAS5319V08-2	thru	NAS5319V08-96	(.1640-32 diameter)
NAS5319V3-2	thru	NAS5319V3-96	(.1900-32 diameter)
NAS5319V4-2	thru	NAS5319V4-96	(.2500-28 diameter)
NAS5319V5-4	thru	NAS5319V5-96	(.3125-24 diameter)
NAS5319V6-4	thru	NAS5319V6-96	(.3750-24 diameter)
NAS5319V8-4	thru	NAS5319V8-96	(.5000-20 diameter)
NAS5319V10-6	thru	NAS5319V10-96	(.6250-18 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4967

Tensile Strength:

160 KSI Min.

Finish Options:

None

example: NAS5319V3-1

Aluminum Coated per NAS4006 and Halogen-free Cetyl Alcohol Lubricant per AS87132, TYPE 3, GRADE B – add “A” after second dash

example: NAS5319V3A10

Heat Treatment Spec:

AMS-H-81200, AMS2801

Drilling Options:

No Hole

example: NAS5319V3-1

Drill Thread for Cotter Pin – add “D” suffix

example: NAS5319V5A15D

Drive Resess:

Six Lobe Recess

For inquiries or to place an order please call us at 718-847-6321.