
NAS5321 Series

100 Degree Flush Head, Alloy Steel, Close Tolerance, Shear Bolts

NAS5321E3-1	thru	NAS5321E3-100	(.1900-32 diameter)
NAS5321E4-1	thru	NAS5321E4-100	(.2500-28 diameter)
NAS5321E5-1	thru	NAS5321E5-100	(.3125-24 diameter)
NAS5321E6-1	thru	NAS5321E6-100	(.3750-24 diameter)
NAS5321E8-1	thru	NAS5321E8-100	(.5000-20 diameter)
NAS5321E10-1	thru	NAS5321E10-100	(.6250-18 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5732, AMS5737, AMS5853

Tensile Strength:

180-210 KSI Min.

Finish:

Passivated per AMS2700, METHOD 1, TYPE 2 or TYPE 8, CLASS 1

example: NAS5321E3-1

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 – add “P” (replace hyphen)

example: NAS5321E3P1

Heat Treatment Spec:

AMS2759, AMS-H-6875

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS5321E3-1

Drill Thread for Cotter Pin – add “D” suffix

example: NAS5321E3-1D

Drive Resess:

Six Lobe Recess

For inquiries or to place an order please call us at 718-847-6321.