
NAS583 thru NAS590 Series

100 Degree Flush Head, Alloy Steel, High Precision Aerospace Bolts

NAS583-2	thru	NAS583-96	(.1900-32 diameter)
NAS584-3	thru	NAS584-96	(.2500-28 diameter)
NAS585-3	thru	NAS585-96	(.3125-24 diameter)
NAS586-3	thru	NAS586-96	(.3750-24 diameter)
NAS587-5	thru	NAS587-96	(.4375-20 diameter)
NAS588-5	thru	NAS588-96	(.5000-20 diameter)
NAS589-5	thru	NAS589-96	(.5625-18 diameter)
NAS590-5	thru	NAS590-96	(.6250-18 diameter)

Material:

Alloy Steel – 4340

Material Spec:

MIL-S-6758

Tensile Strength:

160-180 KSI Min.

Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

MIL-H-6758

Thread Length:

Available in the entire range of standard lengths

Drive Options:

Dovetail Slot Recess per MS33750 –
example: NAS583-1

Offset Cruciform per MS14191 – add “R” suffix
example: NAS583R1

For inquiries or to place an order please call us at 718-847-6321.