

---

## NAS608 Series

---

### Socket Head Cap, Alloy Steel, High Precision Aerospace Screws

NAS608-080-1	thru	NAS608-080-100	(0-80 thread)
NAS608-164-1	thru	NAS608-164-100	(1-64 thread)
NAS608-256-1	thru	NAS608-256-100	(2.56 thread)
NAS608-440-1	thru	NAS608-440-100	(4-40 thread)
NAS608-632-1	thru	NAS608-632-100	(6-32 thread)
NAS608-836-1	thru	NAS608-836-100	(8-32 thread)
NAS608-3-1	thru	NAS608-3-100	(10-32 thread)
NAS608-4-1	thru	NAS608-4-100	(1/4-28 thread)
NAS608-5-1	thru	NAS608-5-100	(5/16-24 thread)
NAS608-6-1	thru	NAS608-6-100	(3/8-24 thread)
NAS608-7-1	thru	NAS608-7-100	(7/16-20 thread)
NAS608-8-1	thru	NAS608-8-100	(1/2-20 thread)
NAS608-10-1	thru	NAS608-10-100	(5/8-18 thread)

---

**Material:**

Alloy Steel – 8740

**Material Spec:**

AMS6322

**Tensile Strength:**

180 KSI Min.

**Hardness:**

37-45 HRC

**Finish Options:**

Black Oxide in Accordance with MIL-DTL-13924, CLASS 1

example: NAS608-080-1

Cadmium Plated per QQ-P-416, TYPE 1, CLASS 3 – add “P” suffix

example: NAS608-080-1P

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 3 – add “T” suffix

example: NAS608-080-1T

**Heat Treatment Spec:**

MIL-H-6875, AMS-H-6875, AS3159

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: NAS608-080-1

Drill Head for Safety Wire – add “H” (replace hyphen)

example: NAS608-080H1

**Locking Options:**

None

example: NAS608-080-1

Optional Type Self-Locking Element – add “LE” (replace hyphen)

example: NAS608-080LE1

Strip Locking Element – add “LL” (replace hyphen)

example: NAS608-080LL1

Button Type Locking Element – add “LN” (replace hyphen)

example: NAS608-080LN1

*For inquiries or to place an order please call us at 718-847-6321.*