
NAS608C Series

Socket Head Cap, CRES, High Precision Aerospace Screws

NAS608C080-1	thru	NAS608C080-100	(0-80 thread)
NAS608C164-1	thru	NAS608C164-100	(1-64 thread)
NAS608C256-1	thru	NAS608C256-100	(2.56 thread)
NAS608C440-1	thru	NAS608C440-100	(4-40 thread)
NAS608C632-1	thru	NAS608C632-100	(6-32 thread)
NAS608C832-1	thru	NAS608C832-100	(8-32 thread)
NAS608C3-1	thru	NAS608C3-100	(10-32 thread)
NAS608C4-1	thru	NAS608C4-100	(1/4-28 thread)
NAS608C5-1	thru	NAS608C5-100	(5/16-24 thread)
NAS608C6-1	thru	NAS608C6-100	(3/8-24 thread)
NAS608C7-1	thru	NAS608C7-100	(7/16-20 thread)
NAS608C8-1	thru	NAS608C8-100	(1/2-20 thread)
NAS608C10-1	thru	NAS608C10-100	(5/8-18 thread)

Material:

CRES – 302, 303, 304

Material Spec:

ASTM-A-493

Tensile Strength:

75 KSI Min.

Hardness:

80 HRB

Finish:

Passivated per QQ-P-35 – add “P” suffix

Heat Treatment Spec:

MIL-H-6875, AMS-H-6875, AS3159

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS608C080-1

Drill Head for Safety Wire – add “H” (replace hyphen)

example: NAS608C080H1

Locking Options:

None

example: NAS608C080-1

Optional Type Self-Locking Element – add “LE” (replace hyphen)

example: NAS608C080LE1

Strip Locking Element – add “LL” (replace hyphen)

example: NAS608C080LL1

Button Type Locking Element – add “LN” (replace hyphen)

example: NAS608C080LN1

For inquiries or to place an order please call us at 718-847-6321.