
NAS609 Series

Socket Head Cap, Alloy Steel, High Precision Aerospace Screws

NAS609-448-1	thru	NAS609-448-100	(4-48 thread)
NAS609-640-1	thru	NAS609-640-100	(6-40 thread)
NAS609-836-1	thru	NAS609-836-100	(8-36 thread)
NAS609-3-1	thru	NAS609-3-100	(10-24 thread)
NAS609-4-1	thru	NAS609-4-100	(1/4-20 thread)
NAS609-5-1	thru	NAS609-5-100	(5/16-18 thread)
NAS609-6-1	thru	NAS609-6-100	(3/8-16 thread)
NAS609-7-1	thru	NAS609-7-100	(7/16-16 thread)
NAS609-8-1	thru	NAS609-8-100	(1/2-13 thread)
NAS609-10-1	thru	NAS609-10-100	(5/8-11 thread)

Material:

Alloy Steel – 8740

Material Spec:

AMS6322

Tensile Strength:

180 KSI Min.

Hardness:

37-45 HRC

Finish Options:

Black Oxide in Accordance with MIL-DTL-13924, CLASS 1

example: NAS609-448-1

Cadmium Plated per QQ-P-416, TYPE 1, CLASS 3 – add “P” suffix

example: NAS609-448-1P

Heat Treatment Spec:

MIL-H-6875, AMS-H-6875, AS3159

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS609-448-1

Drill Head for Safety Wire – add “H” (replace hyphen)

example: NAS609-448H1

For inquiries or to place an order please call us at 718-847-6321.