
NAS609C Series

Socket Head Cap, CRES, High Precision Aerospace Screws

NAS609C448-1	thru	NAS609C448-100	(4-48 thread)
NAS609C640-1	thru	NAS609C640-100	(6-40 thread)
NAS609C836-1	thru	NAS609C836-100	(8-36 thread)
NAS609C3-1	thru	NAS609C3-100	(10-24 thread)
NAS609C4-1	thru	NAS609C4-100	(1/4-20 thread)
NAS609C5-1	thru	NAS609C5-100	(5/16-18 thread)
NAS609C6-1	thru	NAS609C6-100	(3/8-16 thread)
NAS609C7-1	thru	NAS609C7-100	(7/16-16 thread)
NAS609C8-1	thru	NAS609C8-100	(1/2-13 thread)
NAS609C10-1	thru	NAS609C10-100	(5/8-11 thread)

Material:

CRES – 302, 303, 304

Material Spec:

ASTM-A-493

Tensile Strength:

75 KSI Min.

Hardness:

80 HRB

Finish:

Passivated per QQ-P-35 – add “P” suffix

example: NAS609C448-1P

Heat Treatment Spec:

MIL-H-6875, AMS-H-6875, AS3159

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS609C448-1P

Drill Head for Safety Wire – add “H” (replace hyphen)

example: NAS609C448H1P

Locking Options:

None

example: NAS608C080-1

Optional Type Self-Locking Element – add “LE” (replace hyphen)

example: NAS608C080LE1

Strip Locking Element – add “LL” (replace hyphen)

example: NAS608C080LL1

Button Type Locking Element – add “LN” (replace hyphen)

example: NAS608C080LN1

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414