

---

## NAS653 thru NAS658

---

### Hex Head, Titanium, Precision Aerospace Machine Bolts

NAS653V1	thru	NAS653V96	(.1900-32 diameter)
NAS654V1	thru	NAS654V96	(.2500-28 diameter)
NAS655V1	thru	NAS655V96	(.3125-24 diameter)
NAS656V1	thru	NAS656V96	(.3750-24 diameter)
NAS657V1	thru	NAS657V96	(.4375-20 diameter)
NAS658V1	thru	NAS658V96	(.5000-20 diameter)

---

**Material:**

Titanium – 6AL-4V

**Material Spec:**

AMS4928, AMS4967

**Tensile Strength:**

160 KSI Min.

**Finish:**

No Finish (Clean and Degrease)

**Heat Treatment Spec:**

AMS-H-81200 or AMS2801

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: NAS653V1

Drill Shank for Cotter Pin – add “**D**” suffix

example: NAS653V1D

Drill 3 Holes through Head for Safety Wire – add “**H**” suffix

example: NAS653V1H

Drill Head for Safety Wire and Drilled Shank for Cotter Pin – add “**DH**” suffix

example: NAS653V1DH

*For inquiries or to place an order please call us at 718-847-6321.*