
NAS8100 thru NAS8106 Series

Pan Head, Alloy Steel, Cross Recess, Aerospace Screws

NAS8100-1	thru	NAS8100-100	(.1120-40 diameter)
NAS8101-1	thru	NAS8101-100	(.1380-32 diameter)
NAS8102-1	thru	NAS8102-100	(.1640-32 diameter)
NAS8103-1	thru	NAS8103-100	(.1900-32 diameter)
NAS8104-1	thru	NAS8104-100	(.2500-28 diameter)
NAS8105-1	thru	NAS8105-100	(.3125-24 diameter)
NAS8106-1	thru	NAS8106-100	(.3750-24 diameter)

Material:

Alloy Steel – CRES A286

Material Spec:

AMS5731, AMS5737

Tensile Strength:

160 KSI Min.

Finish Options:

Clean and Passivated per QQ-P-35 – add “**U**” (replace hyphen)

example: NAS8103U10

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2 with Green Dye or Paint on the Thread End

– denoted by hyphen “-” example: NAS8103-10

Aluminum Coated per NAS4006 – add “**A**” (replace hyphen)

example: NAS8103A10

Black Oxide Coated per MIL-C-13924, CLASS 3 – add “**B**” (replace hyphen)

example: NAS8103B10

Thread Length:

Full Thread

Self Locking Options:

None

example: NAS8103-10

Self Locking Element – add “**L**” suffix

example: NAS8103L10

Patch Type Locking Element – add “**P**” suffix

example: NAS8103P10

Drive Recess:

Cross Recess per NAS7100

For inquiries or to place an order please call us at 718-847-6321.