
NAS8802 thru NAS8816 Series

100 Degree Reduced Head, Titanium, High Precision Aerospace Bolts

NAS8802-1	thru	NAS8803-100	(.1640-32 diameter)
NAS8803-1	thru	NAS8803-100	(.1900-32 diameter)
NAS8804-1	thru	NAS8804-100	(.2500-28 diameter)
NAS8805-1	thru	NAS8805-100	(.3125-24 diameter)
NAS8806-1	thru	NAS8806-100	(.3750-24 diameter)
NAS8807-1	thru	NAS8807-100	(.4375-20 diameter)
NAS8808-1	thru	NAS8808-100	(.5000-20 diameter)
NAS8809-1	thru	NAS8809-100	(.5625-18 diameter)
NAS8810-1	thru	NAS8810-100	(.6250-18 diameter)
NAS8812-1	thru	NAS8812-100	(.7500-16 diameter)
NAS8814-1	thru	NAS8814-100	(.8750-14 diameter)
NAS8816-1	thru	NAS8816-100	(1.0000-12 diameter)

Material:

Titanium – 6Al-4V

Material Spec:

AMS4928, AMS4957

Tensile Strength:

160-180 KSI Min.

Finish:

No Finish (Clean and Degrease)

example: NAS8802-1

Aluminum Coated per NAS4006 – add “A” (replace hyphen)

example: NAS8802A1

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS8802-1

Drill Shank for Cotter Pin – add “D” (replace hyphen)

example: NAS8802D1

Drive Option:

Phillips Recess

Shank Option:

.0156 Oversize – add “X” suffix

example: NAS8802-1X

.0312 Oversize – add “Y” suffix

example: NAS8802-1Y

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414