
NAS9703 thru NAS9724 Series

Hex Head, Alloy Steel, Close Tolerance, Long Thread, Aerospace Bolts

NAS9703-1	thru	NAS9703-100	(.1900-32 diameter)
NAS9704-1	thru	NAS9704-100	(.2500-28 diameter)
NAS9705-1	thru	NAS9705-100	(.3125-24 diameter)
NAS9706-1	thru	NAS9706-100	(.3750-24 diameter)
NAS9707-1	thru	NAS9707-100	(.4375-20 diameter)
NAS9708-1	thru	NAS9708-100	(.5000-20 diameter)
NAS9709-1	thru	NAS9709-100	(.5625-18 diameter)
NAS9710-1	thru	NAS9710-100	(.6250-18 diameter)
NAS9712-1	thru	NAS9712-100	(.7500-16 diameter)
NAS9714-1	thru	NAS9714-100	(.8750-14 diameter)
NAS9716-1	thru	NAS9716-100	(1.0000-12 diameter)
NAS9718-1	thru	NAS9718-100	(1.1250-12 diameter)
NAS9720-1	thru	NAS9720-100	(1.2500-12 diameter)
NAS9722-1	thru	NAS9722-100	(1.3750-12 diameter)
NAS9724-1	thru	NAS9724-100	(1.5000-12 diameter)

Material:

Alloy Steel – 4140, 4340, 8740

Material Spec:

AMS6832, AMS6415, AMS6484, AMS6325, AMS6327, AMS6322

Tensile Strength:

160-190 KSI Min.

Finish Options:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

Heat Treatment Spec:

AMS2759

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

No Hole

example: NAS9703-1

Drill Shank for Cotter Pin – add “D” suffix

example: NAS9705D

Drill Head for Safety Wire – add “H” suffix

example: NAS9712H1

Drill Head for Safety Wire and Drilled Shank for Cotter Pin

– add “DH” suffix example: NAS9712DH1

For inquiries or to place an order please call us at 718-847-6321.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414