
NASM14157 Series

Flanged External Spline Drive, Steel, Wheel, Tension Bolt

MS14157-04-004	thru	MS14157-04-126	(.2500-28 diameter)
MS14157-05-004	thru	MS14157-05-126	(.3125-24 diameter)
MS14157-06-006	thru	MS14157-06-126	(.3750-24 diameter)
MS14157-07-006	thru	MS14157-07-126	(.4375-20 diameter)
MS14157-08-008	thru	MS14157-08-126	(.5000-20 diameter)
MS14157-09-010	thru	MS14157-09-126	(.5625-18 diameter)
MS14157-10-010	thru	MS14157-10-126	(.6250-18 diameter)
MS14157-12-012	thru	MS14157-12-126	(.7500-16 diameter)
MS14157-14-014	thru	MS14157-14-126	(.8750-14 diameter)

Material:

Alloy Steel – 4140, E4340, 8740

Material Spec:

AMS6382, AMS6415, AMS6484, AMS6322, AMS6325, AMS6327

Tensile Strength:

180 KSI Min.

Hardness:

39-43 HRC

Finish:

Cadmium Plated per NAS672, Supplementary Chromate Treatment per AMS-QQ-416

Thread Length:

Available in the entire range of standard lengths

For inquiries or to place an order please call us at 718-847-6321.