

---

## NASM16995 Series

---

### Socket Hex Head, Cap, 300 Series CRES, Screw

|             |      |             |                     |
|-------------|------|-------------|---------------------|
| MS16995-1   | thru | MS16995-4   | (.0860-56 diameter) |
| MS16995-9   | thru | MS16995-13  | (.1120-40 diameter) |
| MS16995-16  | thru | MS16995-21  | (.1380-32 diameter) |
| MS16995-25  | thru | MS16995-30  | (.1640-32 diameter) |
| MS16995-35  | thru | MS16995-42  | (.1900-24 diameter) |
| MS16995-47  | thru | MS16995-56  | (.2500-20 diameter) |
| MS16995-61  | thru | MS16995-72  | (.3125-18 diameter) |
| MS16995-77  | thru | MS16995-87  | (.3750-16 diameter) |
| MS16995-92  | thru | MS16995-102 | (.5000-13 diameter) |
| MS16995-107 | thru | MS16995-115 | (.6250-11 diameter) |

---

#### Material:

CRES – 304, 304L, 305, 384 or TYPE 18-9LW (any 300 Series Austenitic CRES)  
316 or 316L

#### Material Spec:

UNS S30400, UNS S30403, UNS S30500, UNS S38400, UNS S30430 per ASTM F593  
UNS S31600, UNS S31603

#### Tensile Strength:

80 KSI Min. per FED-STD-H28/2

#### Finish:

Clean and Passivate per AMS2700, METHOD 1, TYPE 6 or TYPE 7, CLASS 1  
example: MS16995-1

Black Oxide in Accordance with MIL-DTL-13924, CLASS 14  
(except for TYPE 316 or TYPE 316L)

– add “**B**” suffix example: MS16995-1B

Unfinished TYPE 316 or TYPE 316L

– add “**S316**” suffix example: MS16995-1S316

*For inquiries or to place an order please call us at 718-847-6321.*