

## NASM20004 thru NASM20024 Series

### Alloy Steel, Precision, Internal Wrenching Bolts

MS20004-4	thru	MS20004-96	(.2500-28 diameter)
MS20005-6	thru	MS20005-96	(.3125-24 diameter)
MS20006-6	thru	MS20006-96	(.3750-24 diameter)
MS20007-8	thru	MS20007-96	(.4375-20 diameter)
MS20008-8	thru	MS20008-96	(.5000-20 diameter)
MS20009-10	thru	MS20009-112	(.5625-18 diameter)
MS20010-10	thru	MS20010-112	(.6250-18 diameter)
MS20012-10	thru	MS20012-112	(.7500-14 diameter)
MS20014-14	thru	MS20014-112	(.8750-14 diameter)
MS20016-16	thru	MS20016-112	(1.0000-14 diameter)
MS20017-17	thru	MS20017-112	(1.0000-12 diameter)
MS20018-18	thru	MS20018-128	(1.1250-12 diameter)
MS20020-20	thru	MS20020-128	(1.2500-12 diameter)
MS20022-22	thru	MS20022-128	(1.3750-12 diameter)
MS20024-24	thru	MS20024-128	(1.5000-12 diameter)

#### Material:

Alloy Steel – 4140, 4340, 8740

#### Material Spec:

AMS6382, AMS6415, AMS6484, AMS6322, AMS6325, AMS6327

#### Tensile Strength:

160 KSI Min.

#### Hardness:

34-40 HRC

#### Finish:

Cadmium Plated per QQ-P-416, TYPE 2, CLASS 2

#### Drilling Options:

No Hole

example: MS20017-18

Drilled Head for Safety Wire – add “H” suffix

example: MS20017-18H

#### Thread Length:

Available in the entire range of standard lengths

*For inquiries or to place an order please call us at 718-847-6321.*