
NASM21 thru NASM37 Series

Slotted Head, Alloy Steel, Precision Aerospace Clevis Bolts

AN21-5	thru	AN21-32	(.1380-40 diameter)
AN22-5	thru	AN22-32	(.1640-32 diameter)
AN23-8	thru	AN23-64	(.1900-32 diameter)
AN24-8	thru	AN24-84	(.2500-28 diameter)
AN25-9	thru	AN25-64	(.3125-24 diameter)
AN26-9	thru	AN26-64	(.3750-24 diameter)
AN27-12	thru	AN27-92	(.4375-20 diameter)
AN28-12	thru	AN28-90	(.5000-20 diameter)
AN29-14	thru	AN29-80	(.5625-18 diameter)
AN30-14	thru	AN30-80	(.6250-18 diameter)
AN32-16	thru	AN32-94	(.7500-16 diameter)
AN34-18	thru	AN34-108	(.8750-14 diameter)
AN37-20	thru	AN37-110	(1.0000-12 diameter)

Material:

Alloy Steel – 4140, 8740

Material Spec:

AMS-S-6758, AMS6322, AMS6325, AMS6327

Finish:

Cadmium Plated per AMS-QQ-P-416, TYPE 2, CLASS 2

Thread Length:

Available in the entire range of standard lengths

Drilling Options:

Drill Hole for Cotter Pin

example: AN21-14

No Hole – add “A” suffix

example: AN21-14A

For inquiries or to place an order please call us at 718-847-6321.