
NASM27576C Series

Hex Head, CRES, Impedance Type, Self-Retaining Bolts

MS27576C3-03	thru	MS27576C3-124	(.1900-32 diameter)
MS27576C4-03	thru	MS27576C4-124	(.2500-28 diameter)
MS27576C5-04	thru	MS27576C5-124	(.3125-24 diameter)
MS27576C6-04	thru	MS27576C6-124	(.3750-24 diameter)
MS27576C7-06	thru	MS27576C7-124	(.4375-20 diameter)
MS27576C8-06	thru	MS27576C8-124	(.5000-20 diameter)
MS27576C9-07	thru	MS27576C9-124	(.5625-18 diameter)
MS27576C10-07	thru	MS27576C10-124	(.6250-18 diameter)
MS27576C12-08	thru	MS27576C12-124	(.7500-16 diameter)
MS27576C14-08	thru	MS27576C14-124	(.8750-14 diameter)
MS27576C16-08	thru	MS27576C16-124	(1.0000-12 diameter)

Material:

CRES Steel – 440C

Material Spec:

AMS-QQ-S-763

Tensile Strength:

95 KSI Min.

Hardness:

36-41 HRC

Finish:

Passivate in accordance with AMS2700, METHOD 1, CLASS 4

Retaining Element:

None

example: MS27576C4-24

Ring Lock Impedance Element – add “**R**” add suffix

example: MS27576C4-24R

Ball Lock Impedance Element – add “**B**” add suffix

example: MS27576C4-24B

Thread Length:

Available in the entire range of standard lengths

For inquiries or to place an order please call us at 718-847-6321.