

---

## NASM42 thru NASM49 Series

---

### Alloy Steel, Eye Bolt

AN42-3	thru	AN42-80	(.1900-32 diameter)
AN43-4	thru	AN43-80	(.2500-28 diameter)
AN44-4	thru	AN44-80	(.3125-24 diameter)
AN45-4	thru	AN45-80	(.3125-24 diameter)
AN46-5	thru	AN46-85	(.3750-24 diameter)
AN47-5	thru	AN47-80	(.4375-20 diameter)
AN48-6	thru	AN48-80	(.5000-20 diameter)
AN49-6	thru	AN49-80	(.5625-18 diameter)

---

**Material:**

Alloy Steel – 4140, 8740, 8735, 4347, 8630

**Material Spec:**

AMS6382, AMS6425, AMS6427, AMS6422, AMS6320, AMS6300, AMS758, AMS6050

**Tensile Strength:**

125 KSI Min.

**Hardness:**

26-32 HRC

**Heat Treatment Spec:**

AMS2759

**Finish:**

Cadmium Plated per AMS-QQ-P-416, TYPE 2, CLASS 3

**Thread Length:**

Available in the entire range of standard lengths

**Drilling Options:**

No Hole

example: AN46-10

Drill Hole in Shank for Cotter Pin – add “A” (replace hyphen)

example: AN46-10A

*For inquiries or to place an order please call us at 718-847-6321.*