

Thinwall Swaged Inserts

Designed for applications requiring lightweight, high strength, compact spaces with a minimum boss. Swaged inserts' high performance benefits most applications requiring dependability in a lightweight solid wall insert. The locking knurl design is easy to install and provides high torque-out performance in soft and hard parent materials and are well-suited for electronics and aircraft engines.

Swaged Inserts

AS3504/5	MIL-I-45932/1-(XX)-L	SRM-(XXX)
AS52760/63	MIL-I-45932/1-(XX)	SRM-(XX)-L-(X)
AS52790/93	MIL-I-45932/2-(XX)-L	SRMW-(X)-(X)
DOD-I-63274/1	MIL-I-45932/2-(XX)	SRMW-(X)-L-(X)
EN3236/7	MIL-I-45932/3-(XX)-L	
NSA5054	MIL-I-45932/3-(XX)	



Insert Removal Tools

MIL-I-45932/1
MIL-I-45932/3

Clinch Nuts and Tools

MIL-N-45938/1
MIL-N-45938/3
MIL-N-45938/13
MIL-N-45938/14
DOD-N-70333/1
DOD-N-70333/2

Slimsert™ Tools

SRM-(X)-D SRPBTM-(X)
SRMW-(X)-D SRWPBTM-(X)
SRM-(X)-W SRPBTM-(X)-WB
SRM-(X)-W2 SRM-GSD-(X)
SRM-(X)-S SRMW-GSD-(X)
SRMW-(X)-S MK4SRM-(X)-AL (kits)
SRM-(X)-R MK5SRM-(X)-BL (kits)



Sizes

#4 through 1/2 inch
5mm-10mm

ID Threads

UNJF
UNJC
Metric

Materials

4130 Alloy Steel
A286
17-4 PH
Alloy 718
(Inconel® 718)

Finishes

Cadmium
per QQ-P-416 Type II, Class 2
Type III, Class 3
Molybdenum Disulfide solid film lubricant
per MIL-L-46010, Type I
Silver
per AMS2411 or QQ-S-365, Type II, Grade B

All of our Inserts are manufactured to **MS, MIL-I, EN, NA, NAS, NASM** and **NSA** standards or they can be modified to meet your specific requirements.

Fastener Dimensions Inc. is an independent distributor of the many brand name products that we sell and that appear in our literature.

* Slimsert™ is a trademark of Alcoa® (AFS).

** Inconel® is a registered trademark of Incoalloys International.

FASTENER DIMENSIONS, INC. ISO9001, AS9100 & AS9120 Certified

6850 River Road, Pennsauken, New Jersey 08110

WEB: WWW.FASTDIM.COM • PHONE: 718-847-6321 • FAX: 718-847-8414